

eSATA RAID Subsystem





SA-3187S

User Friendly, Lowest Total Cost, Easy Management

Arena compact 4bays RAID unit an entry level, user friendly and cost effective solutions designed for small business and SOHO users. With an on-board ASIC, eSATA host connectivity, deliver unsurpassed performance with RAID levels 0, 0+1, 5, and 5+spare. Setup is quick and easy using dip switches accessible from the rear panel. Connecting to the host is plug-and-play, transparent to various operating systems.

FEATURES HIGHLIGHT

Extreme Performance

eSATA provided host-data transfer rate up to 3Gb/s.

Easiest / Quickest Installation

Requires No driver to install, plug and play installation.

User-friendly Management

Front Panel LCD and Buttons, Terminal and In-band GUI, make RAID functions set up and managed in an easier way.

RAID Function

- Easy configuration and access through button and/or dip switch
- Connection through eSATA, connector, without add-on HBA
- RAID Level: 0, 0+1, 5, 5+Spare
- Global Hot spare
- Event Notification









Janus II Series Desktop 4bay eSATA RAID Subsystem









SPECIFICATION

Hardware Components

Model No.	SA-3187S
RAID Controller	Single
No. of Host Channels per Controller	1 x 1.5Gb eSATA
Cache Memory Per Controller	2MB Buffer
No. of Drives	4
Hot Swap Power Supply	1 x 200W
Hot Swap Fan Module	1
Dimension	Desktop 153(W) x 287(D) x 206(H) mm
Weight (without drives)	6 Kgs

Feature Highlights

T catale riiginigitts	
RAID Volume	RAID Level 0, 0+1, 5, 5+spare
	Global and dedicated hot spare
	Online volume expansion
	Auto volume rebuilding
Configuration	Front Panel LCD and Button
Notification	Built-in buzzer
OS Support	Windows; Linux; Mac

Requirements

AC Input	100 to 264V(+/-10%), 47 to 63 Hz	
Operating Temperature	5°C to 40°C	
Humidity	20% to 80% non-condensing	

- * Specifications and product offerings may vary without notice.
 * Various trademarks belong to their respective owners.

TEL: 886-2-2218 4875 FAX: 886-2-2218 4896 http://www.maxtronic.com